

INDEX OF OSM-LUM DECISION SHEETS

October 2019

OPERATIONAL STAFF MEETING LUMINAIRES

No.	SUB-CLAUSE	SUBJECT
EN 60598-1:2015/A1:2018		
DSH 0807A	General	Luminaires system for 230V
DSH 0808A	General	IEC 62262 / EN 50102
DSH 0809A + Fig.	General / 1.7	Fixed luminaire with track
DSH 0810A	General	Metallic paint
DSH 0811A	General	Luminaires for the use with independent control gear
DSH 0813A	General	E27 to G9 and GU10 lampholders adapters
DSH 0814A	General 1.2.60 2.2	T8 to T5, T8 to T8 and similar lamp adaptors (including ditto with LED)
DSH 1086A	General	Insulation class MCPCB material used for LED modules
DSH 0816B	0.2	Socket-outlet mounted rechargeable luminaire Rechargeable lamps luminaires
DSH 0817A + Fig.	0.4	Floodlight with mounting accessories
DSH 0818A	0.4.2	Instruction manual of a floodlight
DSH 0819A	0.4.2 / General	Luminaires needing assembly by the user
DSH 0820A	0.4.2 / 12	Luminaires needing reconnection by the installer
DSH 0821A	0.5	Use of 230V components in 240V luminaires
DSH 0822A	0.5	Series – compensated luminaire (working voltage)
DSH 0823A	0.5	Connecting device with fuse holder
DSH 0824A	0.5	Luminaire marked for lamp GU 5,3
DSH 0402A	0.5	Components

DSH 0403A	0.5	Luminaires provided with socket-outlets
DSH 2004A	0.5	Requirement on batteries as critical component
DSH 2057A	0.5	Simplify the acceptance of replacement of LED modules in luminaires and LED packages/chips in LED modules
DSH 0404A	1.2.60	T5 adapter
DSH 0826A	Sections 2- 3	Classification and marking of Class II with Class III detachable parts
DSH 0827A	3	Definition of basic type reference
DSH 0828A	3	Marking of lamp types according to IEC Technical Specification 61231
DSH 0829A	3	Marking on class III luminaires "system"
DSH 0830A	3.2	Marking on small luminaires
DSH 0831A	3.2.2	Rated voltage marking
DSH 0832A	3.2.6	Marking with IP numbers
DSH 0833A	3.2.6	"IP X8" marking
DSH 0834A	3.2.6 / 9.2	IP test on recessed luminaires
DSH 0835A	3.2.8	Lamp-type information marking
PDSH 2146	3.2.12	Termination marking
DSH 0836A	3.2.13	Symbol for minimum distance from lighted object
DSH 0837A	3.2.16	Protective shields
DSH 0838A	3.3	Markings / additional information
DSH 0839A	3.3.10	Marking – Additional information
DSH 0840A	3.3.7 / 4.24 Annex P	UV radiation
DSH 0841A	4.2 / 8.2.1	Luminaire with fuse holder / fuse
DSH 0842A	4.2 / 15.7	Non-detachable flexible cable or cord
DSH 0843A	4.4.4	Lampholder fixed by the shade ring
DSH 0844A	4.4.4 ii)	Lampholder mounting brackets
DSH 0845A + Fig.	4.7.2	Supply terminals (8 mm free wire)
DSH 0846A	4.7.3	Lampholder terminals
DSH 0847A	4.7.4	Terminals for internal and external connections
DSH 0848A	4.8	Switches for luminaires
DSH 0850A	4.10.1	Double and reinforced insulation

DSH 0851A	4.11.1	Contact pressure
DSH 0852A	4.11 / 4.12	Luminaires to be assembled by user
DSH 0853A	4.11.3	Locking device for screws
DSH 0854A	4.11.3	Screw connections
DSH 0855A	4.11.3	Electrical connections
DSH 0856A	4.11.3 / 7	Crimped connections
DSH 0857A	4.11.3 / 7.2.4	Rivets for electrical and mechanical connections
DSH 0858A	4.11.4	Material with equivalent characteristics
DSH 0859A	4.11.5	Wooden parts on luminaires
DSH 0860A	4.12.4	Portable luminaire; different parts can be loosen by hand
DSH 2121A	4.13	Mechanical strength
DSH 0863A	4.14.1	Clip-mounted luminaire
DSH 0864A	4.14.1	Clip-mounted luminaire: pulling test
DSH 0865A	4.14.3	Screw adjustable by the user
DSH 2002A	4.14.3	Stop rotation adjustable luminaire
DSH 0866A	4.15	Flammable materials
DSH 0867A	4.15	Heated part
DSH 0869A	4.15 / 12.7.1	Application of the linear regression formula
DSH 0870B + Fig.	4.15a) / 12.7.1	Luminaires in thermoplastic material (fixing points)
DSH 0872A	4.16.2 / 12.6.2	Temperature sensing controls
DSH 0873A	4.24	Annex P
DSH 0874A	4.24	Annex P
DSH 0875A	4.24	Use of different M.H. lamps
DSH 0876A	4.24	Protective shield
DSH 2052A	4.24	Optical radiation safety
PDSH 2149	4.29 / 4.30 / 5	Wiring connected via soldering or crimped/twist-on wire connector
DSH 0877A	5.2	Non standardised plug for class III luminaire
DSH 0880A	5.2.2 / 5.3.5	Internal wiring for ordinary luminaires

DSH 0881A	5.2.2 / 7.2.11	Transparent flexible cords
DSH 0882A	5.2.10	Cord anchorage
DSH 2049A	5.2.10.1	LED floodlights
DSH 0883A	5.2.10 / 5.3.5	Cord anchorage on lampholder
DSH 0884A	5.2.10 / 5.3.5	Cord anchorage on adjustable luminaire
DSH 0885A	5.2.10 / 5.3.5	Recessed luminaire delivered with separate control gear
DSH 0887A	5.3	PTFE basic insulated cable
DSH 0888A	5.3	Internal wiring for some lamp circuits
DSH 0889A	5.3.1	Through wiring in the luminaires
DSH 0890A	5.3.3	Use of additional sleeves
DSH 2091A	5.3.5	Use of H03VH7-H 1x0.75 mm ² cables for suspended part of pendant luminaire
DSH 2122A	5.3.5	Cord anchorage
DSH 2050A	7	Connection between metal parts of Class I luminaire and earthing terminal by special fastener fixed to the cover of the luminaire
DSH 0892A	7.2.1	Earthing in luminaire system
DSH 0893A	7.2.1	Electrical connections
DSH 0895B	8	Standard test finger
DSH 0897A	8.2.1	Live metal parts projected from Edison screw caps
DSH 0898A + Fig.	8.2.1 / 8.2	G10q – connector's construction
DSH 0899A	8.2.3	Class II luminaire with metal reflector
DSH 0900A	8.2.3	Metal fixing devices for components
DSH 0901A	8.2.3	Luminaire with PGZ12 lamp cap
DSH 0902A + Fig.	8.2.5	Class II luminaires for discharge lamps
DSH 0903B	9	IP 65 luminaire
DSH 2051A	9	IP recessed luminaire
DSH 0905A	9. / 9.2	IP X3 / IP X4 tests
DSH 0906A	9.2	Torque for fixing screws of covers
DSH 0907A	9.2	Test for ingress of moisture
DSH 2003A	9.2	IP 6X



DSH 0908A + Fig.	9.2 f	Entry of test probes for IP 3X and 4X
DSH 0909A + Fig.	9.2.0	IP 40
DSH 0911A	11	Distances inside a lamp
DSH 0912A	11	Supply terminals – creepage distances and clearances
DSH 0913A	11	Touch lamp
DSH 2034A	11	PTI
DSH 0914B + Fig.	11.2	Creepage and clearances between a metal reflector and the cap of a fluorescent lamp
DSH 0916A	11.2.1	Creepage distances and clearances at a supply terminal
DSH 0918A	12	Endurance and thermal tests
DSH 0919B	12	Luminaires provided with LEDs
DSH 0923A	12.4.1	Temperature limit on terminal block
DSH 0924A	12.4.2	Sleeve for earthing supply cable
DSH 0925B	12.5.1	Abnormal operation condition
DSH 0926A	12.5.1.4)	Luminaire inoperative after the test
DSH 0927A	12.7.1	Fault condition test
DSH 2123A	13.2	Ball pressure test
DSH 0928A	13.2.1	Ball pressure test on soft thermoplastic
DSH 0929A	13.2.1	Temperature for ball pressure test
DSH 0930A	13.3.1	Needle flame test / glow wire test
DSH 2089A	14 - 15	NEMA socket (connector) for luminaires
DSH 0931A	Annex C	Self-ballasted lamps luminaires
DSH 0932A + Table 1	Annex C	Luminaires for M.H. lamps